

**UNITED STATES PATENT APPLICATION**

of

William T. Dalebout

Jeremy Butler

and

Adrian Van Dam

for

SELECTIVELY DYNAMIC EXERCISE PLATFORM

WORKMAN, NYDEGGER & SEELEY
A PROFESSIONAL CORPORATION
ATTORNEYS AT LAW
1000 EAGLE GATE TOWER
60 EAST SOUTH TEMPLE
SALT LAKE CITY, UTAH 84111

THE NEW YORK PUBLIC LIBRARY

BACKGROUND OF THE INVENTION

1. The Field of the Invention

The present invention relates to exercise equipment and more particularly to balancing equipment that provides a dynamic platform on which an individual exercises. The dynamic platform forces the individual to make an effort to maintain his or her balance.

2. The Prior State of the Art

Balancing devices have been developed for recreation and/or exercise that provide an unstable surface on which an individual balances. One such type of balancing device provides an unstable surface through the use of a cylinder that is free to roll on the ground. A board is placed on top of the cylinder and balance is tested as an individual stands on top of the board and attempts to prevent either of the opposing ends of the board from touching the ground. While this balancing device provides an unstable surface, movement of the board is limited to a side-to-side motion.

A second type of balancing device that provides an unstable surface on which to test an individual's balance employs a sphere that is free to roll or pivot in any direction. Such devices generally include some type of board that is placed on or around the object. Balance is tested as an individual stands on top of the board and attempts to prevent any portion of the board from touching the ground. While such balancing devices provide an unstable surface in any direction, frequently the devices are not adaptable to the balancing abilities of individuals.

Another type of balancing device that provides an unstable surface on which to test balance includes a board that pivots about a vertical fulcrum that is connected to a base,

00517 262260

1 which remains stationary on the ground. Balance is tested as an individual stands on top of
2 the board and attempts to prevent any portion of the board from touching any portion of
3 the base. Such balancing devices may allow an individual to increase or decrease the angle
4 along which the board is allowed to pivot prior to touching the base. However, an
5 adjustment mechanism that modifies the pivot angle of the board generally requires the
6 board to be raised or lowered.

SUMMARY OF THE INVENTION

The present invention relates to exercise equipment and more particularly to balancing equipment that provides a selectively dynamic platform on which an individual exercises. The selectively dynamic platform forces the individual to make an effort to maintain balance.

Implementation of the present invention takes place in association with a dynamic platform that provides an unstable surface for an individual. As the individual exercises or moves on the dynamic platform, the weight and/or movement of the individual causes the platform to tilt in a given direction. The individual responds to each tilt in order to attempt to maintain his/her balance. As such, the dynamic nature of the platform causes the individual to work on maintaining balance while performing an exercise.

The dynamic nature of the platform may be selectively adjusted to correspond to the balancing ability of the individual. By way of example, in one implementation a detent adjustment mechanism allows an individual user to select one of a variety of tilt settings. The amount that the platform is allowed to tilt is controlled by adjusting a hub to cause a bottom abutment member set to align with a top abutment member set so as to restrict the amount of tilt achieved when one or more of the top abutment members comes in contact with one or more of the bottom abutment members. The amount of tilt is adjusted without requiring any of the components of the platform to be moved vertically. The dynamic nature of the platform may be further modified through the use of an exercise mechanism coupled to the platform. An example of an exercise mechanism includes handles connected to the platform that increase the movement of the platform and the platform's tendency to throw the individual off balance.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24

Additional features and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by the practice of the invention. The features and advantages of the invention may be realized and obtained by means of the instruments and combinations particularly pointed out in the appended claims. These and other features of the present invention will become more fully apparent from the following description and appended claims, or may be learned by the practice of the invention as set forth hereinafter.

BRIEF DESCRIPTION OF THE DRAWINGS

In order to describe the manner in which the above-recited and other advantages and features of the invention can be obtained, a more particular description of the invention briefly described above will be rendered by reference to specific embodiments thereof which are illustrated in the appended drawings. Understanding that these drawings depict only typical embodiments of the invention and are not therefore to be considered to be limiting of its scope, the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

Figure 1 illustrates an exemplary embodiment of a selectively dynamic platform, in accordance with the present invention and an individual user thereon;

Figure 2 provides an exploded view of the selectively dynamic platform illustrated in Figure 1;

Figure 3 illustrates a mat of the platform of Figures 1 and 2;

Figure 4 illustrates a plate of the platform of Figures 1 and 2;

Figure 5A illustrates a top view of a board of the platform of Figures 1 and 2;

Figure 5B illustrates a bottom view of the board illustrated in Figure 5A;

Figure 6 illustrates a glide ring of the platform of Figures 1 and 2;

Figure 7A illustrates a top view of a connector of the resistance hub of the platform illustrated in Figures 1 and 2;

Figure 7B illustrates a bottom view of the connector illustrated in Figure 7A;

Figure 7C illustrates a cross-sectional view of the connector illustrated in Figure 7A;

Figure 7D illustrates a nut plate of the connector illustrated in Figure 7A;

Figure 7E illustrates an anchor plate of the connector illustrated in Figure 7A;

1 Figure 8A illustrates a top view of a tilt adjuster of the resistance hub of the
2 platform illustrated in Figures 1 and 2;

3 Figure 8B illustrates a bottom view of the tilt adjuster illustrated in Figure 8A;

4 Figure 9 illustrates a base of the platform illustrated in Figures 1 and 2;

5 Figure 10 illustrates a handle that may optionally be used by an individual user in
6 association with a selectively dynamic platform as illustrated in Figure 1;

7 Figure 11A illustrates a top view of another embodiment of a board of the platform
8 of Figures 1 and 2;

9 Figure 11B illustrates a bottom view of another embodiment of a board of the
10 platform illustrated in Figures 1 and 2;

11 Figure 12A illustrates a top view of another embodiment of a connector of the
12 resistance hub of the platform illustrated in Figures 1 and 2;

13 Figure 12B illustrates a bottom view of the embodiment of the connector illustrated
14 in Figure 12A;

15 Figure 12C illustrates a cross-sectional view of the embodiment of the connector
16 illustrated in Figure 12A;

17 Figure 12D illustrates another embodiment of a nut plate of the connector;

18 Figure 12E illustrates a cross-sectional view of another embodiment of the
19 connector; and

20 Figure 12F illustrates another embodiment of an anchor plate of the connector.
21
22
23
24

Docket No. 13914.632

Therefore, embodiments of the present invention are associated with a dynamic platform that provides an unstable surface for an individual. As the individual exercises or moves on the dynamic platform, the platform is allowed to tilt in a given direction. The user selectively adjusts the amount that the platform is allowed to tilt by aligning a flexible connector with a tilt adjuster, such as through the use of aligned abutment members or

1 through another system that adjusts tilt. The dynamic nature of the platform can be further
2 adjusted through the use of handles held by the individual user.

3 The following disclosure, corresponding to Figures 2 – 10, provides additional
4 details as to the various components of an exemplary embodiment of the present invention.
5 Figure 2 is an exploded view of an embodiment of the present invention and Figures 3 – 9
6 correspond to individual components of the embodiment of Figure 2. Furthermore, Figure
7 10 provides an exemplary handle that may optionally be used in association with the
8 embodiment illustrated in Figure 2.

9 Referring now to Figure 2, an exploded view of dynamic platform 12 is illustrated.
10 The components of dynamic platform 12 include fastening devices 20 (e.g., screws, bolts,
11 etc.) a mat 22, a plate 24, a board 26, a glide ring 28, a two-part flexible adjustable hub 29,
12 and a base 34. Hub 29 comprises (i) a flexible connector 30 and (ii) a tilt adjuster 32, as
13 discussed above. One or more fastening devices 20 may be used to secure mat 22, plate
14 24, board 26, and glide ring 28 to connector 30. Optionally, an adhesive is employed or
15 the parts are formed as an integral unit, for example, although other alternatives are
16 available, as will be appreciated by one skilled in the art in light of the disclosure herein.
17 Base 34 and tilt adjuster 32 are secured to connector 30 through the use of anchor bolts 112
18 that are molded into connector 30.

19 Those skilled in the art will appreciate that a variety of different types of fastening
20 devices 20 may be used to secure various components of a dynamic platform together,
21 such as screws, bolts, pins, and the like. Furthermore, an adhesive may be used with or
22 without fastening devices 20 to secure a plurality of components together. By way of
23 example, an adhesive may be placed between the underneath surface of mat 22 and the top
24

Docket No. 13914.632

1 Referring now to Figure 4, an exemplary illustration is provided of a reinforcing
2 plate illustrated as plate 24, which may be used as a component of dynamic platform 12 of
3 Figure 1. Plate 24 is used as a reinforcement to distribute the force that is applied to the
4 center of dynamic platform 12. Apertures 50a – 50c of plate 24 correspond to apertures
5 42a – 42d of mat 24 (Figure 3) through which fastening devices 20 (Figure 2) may be
6 inserted. Plate 24 can be made from any material that would provide strength to the
7 dynamic platform, such as steel.

8 Referring now to Figures 5A and 5B, an illustration is provided of an exemplary
9 board, illustrated as board 26, which may be used as a component of dynamic platform 12
10 of Figure 1. Figure 5A illustrates a top view and Figure 5B illustrates a bottom view of
11 board 26. A central, upper portion 60 of board 26 is recessed below the top surface 61 of
12 board 26 so as to allow plate 24 (Figure 4) to reside therein. When inserted, the top
13 surface of plate 24 is flush with the top surface 61 of board 26. Furthermore, apertures 62a
14 – 62d correspond to apertures 50a – 50d of plate 24 (Figure 4) and apertures 42a – 42d of
15 mat 22 (Figure 3) to allow fastening devices 20 (Figure 2) to be inserted therethrough.
16 Board 26 is made out of a durable material, such as hanna resin (“ABS 433”) or the
17 equivalent, which resists fracture when dynamic platform 12 is in use. Grooves 64a – 64h
18 of board 26 correspond to grooves 44a – 44h of mat 22 (Figure 3) to provide various
19 locations for which handles 18 (Figure 1) may be selectively attached.

20 An individual may stand either along the long axis or the short axis of board 26.
21 As illustrated in Figure 5B, the lower portion of board 26 is reinforced with a rib structure
22 that provides strength to keep board 26 from deforming and/or fracturing. The rib
23 structure includes oval ribs 66, lateral ribs 68, long-axis ribs 70, short-axis ribs 72, and
24 central ribs 74 which are coupled to the upper surface of board 26. Oval ribs 66 provide an

1 even support and to give rigidity to board 26. Lateral ribs 68 provide lateral strength to
2 board 26. Long-axis ribs 70 provide support along the long axis of board 26. Similarly,
3 short-axis ribs 72 provide strength across the short axis of board 26. Central ribs 74
4 radially distribute the force that is applied at the center of board 26 to prevent a centralized
5 force strain at the center of board 26.

6 Referring now to Figure 6, an exemplary illustration is provided of a friction
7 reducer, illustrated as glide ring 28, which may be used as a component of dynamic
8 platform 12 of Figure 2. Glide ring 28 is made out of delrin, nylon, high-density
9 polyethylene, high-density polypropylene, or the like to provide a friction-free
10 environment between board 26 and connector 30. Figure 6 illustrates the bottom view of
11 glide ring 28 so as to illustrate protrusions 80a – 80d, which insert into apertures of
12 connector 30 to maintain glide ring 28 adjacent to connector 30, as will be further
13 explained below.

14 Referring now to Figures 7A – 7C, an exemplary illustration is provided of flexible
15 connector 30. Figure 7A illustrates a top view, Figure 7B illustrates a bottom view, and
16 Figure 7C illustrates a cross-sectional view. As illustrated in Figure 7C, connector 30
17 comprises: (i) a flexibly dynamic body 111; and (ii) an anchor 112 and nut plate 110
18 coupled to body 111. In one embodiment, nut plate 110 and anchor 112 are molded
19 inserts. Nut plate 110 is used for receiving fastening devices 20 (Figure 2), thus securing
20 mat 22, plate 24 and board 26 to connector 30. Anchor 112 is used for fastening connector
21 30 to base 34. Nut plate 110 and anchor 112 are illustrated independently from body 111
22 in Figures 7D and 7E, respectively.

23 Dynamic body 111 comprises a flexible material that allows board 26 to tilt in any
24 direction. Examples of such flexible materials include a material latex, a polyurethane, a

1 synthetic rubber, etc. In a further embodiment, the synthetic rubber used for the dynamic
2 body 111 is butal with a durometer 50 shore A.

3 As illustrated in Figure 7C, body 111 comprises (i) a central portion 95; and (ii) a
4 wing portion 96 extending outwardly from and surrounding central portion 95. Nut plate
5 110 is coupled to an upper end of central portion 95, such as by being embedded therein.
6 An upper ring 97 of flexible material is mounted on top of nut plate 110. In one
7 embodiment, ring 97 comprises the same material that is employed for body 111. Anchor
8 112 is coupled to a lower end of central portion 95 of body 111, as shown in Figures 7B
9 and 7C, such that anchor bolts 132c – 132d (Figure 7B) protrude from body 111.

10 Glide ring 28, having protrusions 80a – 80d (Figure 6), resides on the top surface of
11 wing portion 96 (Figure 7A) and is affixed by lodging protrusions 80a – 80d into
12 corresponding apertures 94a – 94d (Figure 7A) of wing portion 96. In a further
13 embodiment an adhesive is used to further secure protrusions 80a – 80d in apertures 94a –
14 94d. Glide ring 28 provides a friction-free surface between connector 30 and board 26.

15 Connector 30 is coupled to board 26 and base 32. A male portion 90 of connector
16 30 (Figure 7A) is inserted into a female portion 76 of board 26 (Figure 5B). Apertures 92a
17 – 92d of ring 97 (Figures 7A and 7C) correspond to apertures 62a – 62d of board 26
18 (Figure 5A), which correspond to apertures of plate 24 (Figure 4), and mat 22 to allow for
19 fasteners 20 (Figure 2) to be inserted therethrough. Thus, connector 30 is coupled to board
20 26. Anchor 112 couples connector 30 to base 34, as discussed below.

21 As illustrated in Figure 7B, connector 30 also includes a set of abutment members
22 100a – 100d that mount to the underneath surface of wing portion 96. Abutment members
23 100a – 100d are an example of the top abutment members referred to above in the
24 discussion corresponding to Figure 1. In one embodiment, abutment members 100a –

1 100d are approximately two inches in width and have a tapered angle of 23°, although a
2 variety of different configurations are available. A mating bottom abutment member from
3 tilt adjuster 32 (Figure 8a) aligns with a respective abutment member 100 from connector
4 30 to limit the amount of tilt the dynamic platform 12 is able to achieve. Receiving
5 sockets 102 are configured to selectively receive protrusions extending from a portion of
6 tilt adjuster 32 in order to align a set of bottom abutment members with abutment members
7 100, as discussed below.

8 Figure 7D illustrates a bottom view of a first insert (optionally molded) that is
9 referred to above as nut plate 110. Plate 110 includes dimpled protrusions 120a – 120h
10 that create surface area to which dynamic body 111 of connector 30 may adhere during a
11 molding process in order to form a reliable bond between nut plate 110 and body 111. In
12 one embodiment, four of the protrusions, e.g., protrusions 120a – 120d, are internally
13 threaded to allow a fastening device 20 (Figure 2) to be attached thereto in order to couple
14 board 26 to connector 30. The internally threaded protrusions 120a – 120d correspond to
15 apertures 92a – 92d of ring 97 (Figure 7A), apertures 62a – 62d of board 26 (Figure 5A),
16 apertures 50a – 50d of plate 24 (Figure 4) and apertures 42a – 42d of mat 22 (Figure 3). In
17 one embodiment, as the fastening devices 20 extend down through the board 26 and into
18 the connector 30, a bonding agent, such as an adhesive, is applied to eliminate any twisting
19 between the fastening devices 20 and body 111 of connector 30 to ensure that all
20 movement takes place uniformly.

21 Figure 7E illustrates a second insert (optionally molded), referred to above as
22 anchor 112, which includes a steel plate 130 and anchor bolts 132a – 132d coupled thereto.
23 In one embodiment, each anchor bolt 132 is made up of a 5/16th-threaded rod that is bent
24 on a 90° angle with a portion (e.g., 1.37 inches) of the bolt sticking out from the bottom

surface of anchor plate 130. Anchor bolts 132a – 132d are tack welded to each other and to anchor plate 130 so as to ensure that each anchor bolt 132 maintains its position. The top surface of anchor plate 130 and any portion of anchor bolts 132a – 132d above the top surface of anchor plate 130 are coupled to dynamic body 111 of connector 30, as illustrated in Figure 7C, such as through a molding process. The portions of anchor bolts 132 that protrude out of the bottom of connector 30 (Figure 7B) are affixed to a stationary base 34. Bolts 132 may comprise a variety of different fasteners, such as bolts, threaded screws, pins, etc.

Referring now to Figures 8a and 8b, exemplary illustrations are provided of tilt adjuster 32 which may be used as a component of dynamic platform 12 of Figure 2. Figure 8a is a top view and Figure 8b is a bottom view of adjuster 32. Connector 30 and adjuster 32 are movably coupled to each other such that adjuster 32 may rotate about lower end 103 of connector 30 (Figure 7B).

The rotation of tilt adjuster 32 allows for the selective adjustment of the dynamic nature of platform 12. Tilt adjuster 32 includes (i) a circular body 139; and (ii) handles 140a – 140d coupled to body 139 to facilitate a user in rotating tilt adjuster 32 in either a clockwise or counter clockwise direction. As a user rotates tilt adjuster 32, protrusions 142a – 142d, located on the interior diameter of body 139 opposite handles 140 as illustrated in Figures 8a – 8b, move from one set of receiving sockets 102 of connector 30 (Figure 7B) to another set of sockets 102. Each time the protrusions 142 interlockingly mate with a set of sockets 102, a set of bottom abutment members of adjuster 32 is aligned underneath abutment members 100 of connector 30 (Figure 7B). The combination of sockets 102 and protrusions 142 provides an example of a selectively interlocking detent mechanism.

1 Figure 8a illustrates three sets of abutment members on tilt adjuster 32, namely
2 abutment members 144a –144d, abutment members 146a – 146d and abutment members
3 148a –148d. Each set of abutment members of tilt adjuster 32 restricts the amount of tilt
4 that board 26 (Figure 2) can undergo. Therefore, by way of example, when board 26 tilts
5 in a given direction, the tilt causes one or more abutment members 100 of connector 30 to
6 come into contact with one or more corresponding abutment members 144a – 144d, 145A
7 – 145d or 148a – 148d of adjuster 32 in order to restrict any further tilting of board 26.

8 The varying size of the three sets of abutment members of tilt adjuster 32 allows for
9 selectable settings of the dynamic nature of platform 12. Abutment members 144 are the
10 tallest of the three sets of abutment members of tilt adjuster 32 and therefore provide the
11 greatest amount of restriction to the tilting of board 26. In contrast, abutment members
12 148 are the shortest of the three sets of abutment members of tilt adjuster 32 and therefore
13 provide the least amount of restriction to the tilting of board 26. Abutment members 146
14 are a height between the heights of abutment members 144 and 148 to provide a tilt
15 restriction between the tilt restriction caused by abutment members 144 and the tilt
16 restriction caused by abutment members 148. Therefore, the tilt restriction of dynamic
17 platform 12 is selectable by rotating tilt adjuster 32 so as to select one of the sets of
18 abutment members of adjuster 32 to align or correspond to abutment members 100 of
19 connector 30 (Figure 7B). While the illustrated embodiment of adjuster 32 includes three
20 sets of abutment members to provide three settings of tilt restriction, other embodiments of
21 the present invention include less than three or more than three settings of tilt restriction.

22 The moving of protrusions 142 from one set of sockets 102 to another set of
23 sockets 102 aligns a set of abutment members 144, 146 or 148 of adjuster 32 with the
24 abutment members 100 of connector 30 (Figure 7B). As a user rotates adjuster 32,

1 protrusions 142 (Figure 8a) enter and exit corresponding sockets 102 (Figure 7B) for each
2 rotational setting.

3 Figure 9 illustrates an exemplary embodiment of a stationary support base,
4 illustrated as base 34, which can be used as a component of the exemplary embodiment
5 illustrated in Figure 2. Base 34 includes a set of legs 150, a central plate 152 and a set of
6 feet 154. One end of each of legs 150 is tack welded to central plate 152 and opposing
7 ends of legs 150 are each fastened to a respective foot 154. Central plate 152 includes
8 apertures 156a – 156d that correspond to and couple with anchor bolts 132a – 132d of
9 connector 30 (Figure 7C). The coupling of anchor bolts 132 through apertures 156 couples
10 connector 30 to tilt adjuster 32 and base 34. For example, bolts 132a – 132d may have
11 threads thereon which are threadedly coupled to base 34 or may be welded to base 34.
12 Adjuster 32 is movably coupled to connector 30 and selectively rotates about connector 30.

13 The dynamic nature of platform 12 may also be adjusted through the use of an
14 exercise mechanism coupled to the platform 12. Examples of an exercise mechanism
15 coupled to platform 12 include one or more handles, a cord and pulley system, or any other
16 exercise mechanism that may be coupled to any portion of platform 12 (e.g., top, bottom,
17 and/or within). The exercise mechanism may be coupled to platform 12 such that the
18 exercise mechanism is on top of, underneath or within the platform and can be employed
19 by the individual on the platform.

20 In Figure 10, an illustration is provided of an exemplary embodiment of a handle,
21 illustrated as handle 18, which includes grip 160 coupled to a linkage 162 that is in turn
22 coupled to a first end 163 of an elastic member 164. A abutment member 166 is placed
23 about an opposite end 165 of elastic member 164 and a male end of a plunger 168 is
24 inserted into the end 165 of the elastic member 164 so as to hold the end 165 between the

plunger 168 and the abutment member 166. When abutment member 166, end 165 and plunger 168 are coupled, abutment member 166 may be selectively inserted into one of the various grooves 64 of board 26 (Figure 5A) so as to be used while the individual performs an exercise workout on dynamic platform 12.

As illustrated in Figure 1, an individual 10 on top of dynamic platform 12 may employ an exercise mechanism, such as by pulling one or more handles 18, to increase the dynamic nature of board 26. Therefore, the use of handles 18 further increases the tilting nature of board 26. While Figure 1 illustrates the use of two handles 18a – 18b, other embodiments of the present invention allow for the use of more than two handles, the use of one handle, or the use of no handles. The stretchable, elastic handles 18 of one embodiment allow the user to increase the dynamic nature of the platform, rather than assisting the user in stabilizing the board.

With reference now to Figures 11A – 12F, illustrations are provided of additional embodiments of various components of platform 12 (Figure 2). Figures 11A – 11B correspond to additional embodiments of a board that may be used as a component of platform 12. Figures 12A – 12F correspond to additional embodiments of connectors that may be used as a component of platform 12.

In Figure 11A, an illustration is provided of a top view of board 26a, which is another embodiment of a board used as a component of platform 12. Board 26a includes one or more recesses (e.g., oval recesses) on the top surface of board 26a into which a mating decorative insert (e.g., a decal) may be coupled.

In Figure 11B, an illustration is provided of a bottom view of board 26b, which is yet another embodiment of a board used as a component of platform 12. Board 26b includes another configuration of a rib structure, as compared to the rib structure of board

26 illustrated in Figure 5b, which provides strength to keep board 26b from deforming and/or fracturing. The illustrated rib structure of board 26b includes oval ribs, lateral ribs, long-axis ribs, short-axis ribs, and central ribs that are coupled to the upper surface of board 26b. The rib structures of Figures 5B and 11B provide structural examples for providing the necessary strength to the board to prevent the board from deforming and/or fracturing while in use.

As provided above, Figures 12A – 12F provide various additional embodiments of connectors that may be used as a component of platform 12. One embodiment, illustrated in Figures 12A – 12C includes connector 30a, which comprises a solid dynamic body 111a (Figure 12C). The top, bottom and cross-sectional views of connector 30a are respectively illustrated in Figures 12A, 12B and 12C.

Connector 30a includes a nut plate, illustrated as nut plate 110a, for coupling connector 30a to the board of the platform, and an anchor plate for coupling connector 30a to the base of the platform. In one embodiment, nut plate 110a comprises four protrusions that are internally threaded to allow a fastening device 20 (Figure 2) to be attached thereto in order to couple board 26 to connector 30a.

Another embodiment, illustrated in Figure 12E, includes connector 30b that comprises a nut plate, an anchor plate and a cavity 131. The anchor plate illustrated is anchor plate 112a (Figure 12F), which provides an opening to cavity 131. The illustrated embodiments of the present invention include a two-part hub that comprises (i) a flexible connector flexibly connecting the board to the base of the platform, and (ii) a tilt adjuster placed about the connector to restrict the amount of tilt achieved by the platform to a desired, adjusted amount. As provided above, other embodiments in accordance with the

1 to further increase the dynamic nature of the platform. As such, an individual may test his
2 or her balance or increase his or her exercise workout by doing so on top of the selectively
3 dynamic platform.

4 As mentioned, the abutment members of the present invention may have a variety
5 of different shapes. For example, in one embodiment, the top portions of lower abutment
6 members 144, 146 and/or 148 are flattened while the lower portions thereof retain the
7 angled wedge shape shown. Flattening the upper tips of these members may allow the
8 adjuster to be moved more freely about the connector. However, the abutment members
9 may have a variety of different shapes that achieve the objects described herein.

10 The present invention may be embodied in other specific forms without departing
11 from its spirit or essential characteristics. The described embodiments are to be considered
12 in all respects only as illustrative and not restrictive. The scope of the invention is,
13 therefore, indicated by the appended claims rather than by the foregoing description. All
14 changes which come within the meaning and range of equivalency of the claims are to be
15 embraced within their scope.

16 What is claimed and desired to be secured by United States Letters Patent is:
17
18
19
20
21
22
23
24